

<b>Cylinders</b>			2		
<b>Bore</b>			1,97	in	50 mm
<b>Stroke</b>			1,14	in	29 mm
<b>Displacement</b>			6,95 cu	in	113,9 cm <sup>3</sup>
<b>Rated speed</b>			2520	rpm	2520 min <sup>-1</sup>
<b>Max. working pressure</b>			135	psi	9,3 bar
<b>Air displacement</b>			10,13	cfm	287 l/min
<b>Oil free</b>			0,0	gal	0,00 lt
<b>Maximum tank capacity</b>			50	l	
<b>F.A.D (Free air delivery)</b>	At	psi	20	cfm	7,91
	At	psi	40	cfm	6,67
	At	psi	70	cfm	4,77
	At	psi	90	cfm	3,74
	At	psi	100	cfm	3,32
	At	psi	116	cfm	2,65
<b>OUTPUT AIR</b>	At	bar	1,4	l/min	224
	At	bar	2,8	l/min	189
	At	bar	4,8	l/min	135
	At	bar	6,2	l/min	106
	At	bar	6,9	l/min	94
	At	bar	8	l/min	75



## DOUBLE CYLINDER COMPRESSOR Data Sheet

<b>Motor power</b>	4	CV	PEAK		
<b>Input power</b>	1350	Watt	PEAK		
<b>Power supply</b>	230 V	50/60 Hz	1 ~		
	120 V	50/60 Hz	1 ~		
	100 V	50-60Hz	1 ~		
<b>Rated supply</b>	7 Ampere	At	230 V	50/60 Hz	1 ~
	14 Ampere	At	120 V	50/60 Hz	1 ~
	15 Ampere	At	100 V	50/60 Hz	1 ~
<b>Capacitor</b>	V	50/60Hz	1 ~	0 uf	0 V
<b>Insulation class</b>	F				
<b>Weight</b>	13,2	lbs			
<b>Dimensions</b>	9,84	In	250 mm L		
	9,84	In	250 mm P		
	7,87	In	200 mm H		

**Thermal protection wit automatic reset**